



ETI™ FS143 (Cast-gloss Paper)  
 ETI™ AD13 (Permanent Adhesive)  
 ETI™ SC2 (Silicone)  
 ETI™ LN70 (White Glassine)

**Facestock**

ETI™ FS143 features high brightness and a blue-white shade, combined with a cast coated, high gloss finish. It has a good adhesive receptivity.

<b>Basis weight*</b>	0,016 lbs/ft <sup>2</sup> or 80 g/m <sup>2</sup>
<b>Brightness</b>	87%
<b>Gloss</b>	40%
<b>Opacity</b>	86%

\*Available in other basis weights

**Adhesive**

ETI™ AD13 is a medium viscosity permanent adhesive for crystal clear, no-look label applications. It has a good balance of machining properties including good coatability and clean die cutting.

<b>Application Temperatures</b>	300 to 350 °F or 150 to 175°C
<b>Service Temperatures</b>	-5 to 175°F or -20 to 80 °C

**Silicone**

ETI™ SC2 is a silicone coating enabling different release possibilities.

**Liner**

ETI™ LN70 is a white glassine for two sides siliconizing applications.

<b>Caliper*</b>	0,0022 in. or 0,0057 cm ± 10%
<b>Basis Weight*</b>	0,0133 lbs/ft <sup>2</sup> or 65 g/m <sup>2</sup>

\*Other calipers and basis weights also available

**Statement of practical use**

As with all pressure-sensitive materials, this product should be tested thoroughly under end-use conditions to ensure it meets the requirements of the specific application.

**Performance data**

**Peel Adhesion**

<b>Stainless steel</b>	2,2 lbs	or 1,00 kg
<b>HDPE</b>	2,3 lbs	or 1,04 kg
<b>Polypropylene</b>	2,3 lbs	or 1,04 kg
<b>Glass</b>	2,4 lbs	or 1,09 kg

**Loop Tack**

<b>Stainless steel</b>	2,5 lbs	or 1,13 kg
<b>HDPE</b>	2,1 lbs	or 0,95 kg
<b>Polypropylene</b>	2,1 lbs	or 0,95 kg
<b>Glass</b>	2,4 lbs	or 1,09 kg

<b>Total Construction Caliper (approximate)</b>	0,0065 in. or 0,00165 cm ± 10%
---	--------------------------------

<b>*3 possibilities of release</b>	High
	Medium
	Low

**Additional Information :**

**Printing and Converting**

Printable directly on the facestock in all classical processes processes : flexographic, gravure, silk screen, UV letterpress processes. Excellent conversion characteristics in rotary and flat-bed.

**Application and uses**

This label is designed for label applications where high gloss, cast coated sheet is necessary. This general purpose product is generally used in wine and spirit labels.

**Shelf Life**

One year when stored at 72°F at 50% RH.