

	ETI™ SC2 (Silicone)
	ETI™ FS174 (Semi-gloss Paper)
	ETI™ AD24 (Removable adhesive)

**Facestock**

ETI™ FS174 is a one side coated, semi-gloss supercalendered paper.

<i>Caliper</i>	0,0026 in.	or 0,0066 cm ± 10%
<i>Basis weight</i>	0,016 lbs/ft <sup>2</sup>	or 78 g/m <sup>2</sup>
<i>Brightness</i>	90%	
<i>Gloss</i>	70%	
<i>Opacity</i>	87%	

**Adhesive**

ETI™ AD24 is an adhesive removable with warm and soapy water. It has a fast remoistening tack and speed.

<i>Type</i>	Removable
<i>Application Temperatures</i>	275 to 350 °F or 150 to 175 °C
<i>Service Temperatures</i>	-5 to 175 °F or -20 to 80 °C

**Silicone**

ETI™ SC2 is a silicone coating.

**Additional Information :**

**Printing and Converting**

Printable directly on the facestock in all classical processes : flexographic, gravure, silk screen, UV letterpress processes. Excellent conversion characteristics in rotary and flat-bed.

**Application and uses**

This high-quality multipurpose label paper is designed for multicolor labels requiring good print definition and fine detail. This product is recommended for applications where clean removability is important.

**Shelf Life**

One year when stored at 72°F at 50% RH.

**Statement of practical use**

As with all pressure-sensitive materials, this product should be tested thoroughly under end-use conditions to ensure it meets the requirements of the specific application.