

	ETI™ SC1 (Silicone)
	ETI™ FS142 (Semi-gloss Paper)
	ETI™ AD25 (Removable adhesive)

### Facestock

ETI™ FS142 is a semi-gloss paper designed for wet strength label applications with a blue-white shade. It is one-side coated and it has a high brightness and opacity for good label appearance.

<i>Caliper</i>	0,0026 in.	or 0,0066 cm ± 10%
<i>Basis weight</i>	0,016 lbs/ft <sup>2</sup>	or 80 g/m <sup>2</sup>
<i>Tensile strength TD</i>	13,70#/in.	or 2,4 kN/m
<i>Tensile strength MD</i>	26,27#/in.	or 4,6 kN/m
<i>Gloss</i>	90%	
<i>Opacity</i>	87%	

### Adhesive

ETI™ AD25 is a removable and remoistenable adhesive. It has a fast remoistening tack and speed.

<i>Type</i>	Removable
<i>Application Temperatures</i>	275 to 350 °F or 150 to 175 °C
<i>Service Temperatures</i>	-5 to 175 °F or -20 to 80 °C

### Silicone

ETI™ SC3 is a silicone coating.

### Additional Information :

#### Printing and Converting

Printable directly on the facestock in all classical processes : flexographic, gravure, silk screen, UV letterpress processes. Excellent conversion characteristics in rotary and flat-bed.

#### Application and uses

This high quality multipurpose label paper is designed for multicolor labels requiring good print definition and fine detail. This product is recommended for applications where clean removability is important.

#### Shelf Life

One year when stored at 72°F at 50% RH.

### Statement of practical use

As with all pressure-sensitive materials, this product should be tested thoroughly under end-use conditions to ensure it meets the requirements of the specific application.